<u>GC01002</u> OPERATING CODE 1 LEGAL TEXT DATED 09/01/2018

OPERATING CODE NO. 1

(OC1)

DEMAND FORECASTS

CONTENTS

(This contents page does not form part of the Grid Code)

Paragraph No/Title	Page Number	
OC1.1 INTRODUCTION	22	Formatted: Font: Calibri, 11 pt
OC1.2 OBJECTIVE		Formatted: Font: Calibri, 11 pt
OC1.3 SCOPE		Formatted: Font: Calibri, 11 pt
OC1.4 DATA REQUIRED BY NGET IN THE OPERATIONAL PLANNING PHASE	22	Formatted: Font: Calibri, 11 pt
OC1.5 DATA REQUIRED BY NGET IN THE PROGRAMMING PHASE, CONTROL PH	IASE AND	
POST-CONTROL PHASE	3	Field Code Changed
OC1.6 NGET FORECASTS		Formatted: Font: Calibri, 11 pt
		Formatted: Font: Calibri, 11 pt
A		Formatted: Font color: Auto

17 August 2012

OC1.1 INTRODUCTION

- OC1.1.1 **Operating Code No.1** ("**OC1**") is concerned with **Demand** forecasting for operational purposes. In order to match generation output with **Demand** for electricity it is necessary to undertake **Demand** forecasting. It is also necessary to undertake **Demand** forecasting of **Reactive Power**.
- OC1.1.2 In the **Operational Planning Phase**, **Demand** forecasting shall be conducted by **NGET** taking account of **Demand** forecasts furnished by **Network Operators**, who shall provide **NGET** with information in the form set out in this **OC1**. The data supplied under the **PC** is also taken into account.
- OC1.1.3 In the **Programming Phase** and **Control Phase**, **NGET** will conduct its own **Demand** forecasting taking into account information to be furnished by **Suppliers** and **Network Operators** and the other factors referred to in OC1.6.1.
- OC1.1.4 In this OC1, the point of connection of the External Interconnection to the National Electricity Transmission System shall be considered as a Grid Supply Point. Reactive Power Demand includes the series Reactive losses of the User's System but excludes any network susceptance and any Reactive compensation on the User's System. NGET will obtain the lumped network susceptance and details of Reactive compensation from the requirements to submit data under the PC.
- OC1.1.5 Data relating to **Demand Control** should include details relating to MW.
- OC1.1.6 OC1 deals with the provision of data on Demand Control in the Operational Planning Phase, the Programming Phase and the Post-Control Phase, whereas OC6 (amongst other things) deals with the provision of data on Demand Control following the Programming Phase and in the Control Phase.
- OC1.1.7 In this OC1, Year 0 means the current Financial Year at any time, Year 1 means the next Financial Year at any time, Year 2 means the Financial Year after Year 1, etc.
- OC1.1.8 References in **OC1** to data being supplied on a half hourly basis refer to it being supplied for each period of 30 minutes ending on the hour and half-hour in each hour.

OC1.2	OBJECTIVE		Formatted: Font color: Auto
	The objectives of OC1 are to:		
OC1.2.1	enable the provision of data to NGET by Users in the and Post-Control Phase; and	Programming Phase, Control Phase	
OC1.2.2	provide for the factors to be taken into account by N Programming Phase and Control Phase .	GET when Demand forecasting in the	
OC1.3	SCOPE		Formatted: Font color: Auto
	OC1 applies to NGET and to Users which in this OC1	means:	
	(a) Network Operators, and		
	(b) Suppliers.		
OC1.4	DATA REQUIRED BY NGET IN THE OPERATIONAL	PLANNING PHASE	Formatted: Font color: Auto
OC1.4.1	 (a) Each User, as specified in (b) below, shall provid OC1.4.2 below. 	e NGET with the data requested in	
	(b) The data will need to be supplied by each Netwo National Electricity Transmission System in re- relation each Generator with respect to the outpu Stations within its System.	elation to Demand Control and in	
OC1.4.2	(a) <u>Data</u>		
Issue 5 Revision	0 OC1 2 of 5	17 August 2012	

Formatted: Font: 10 pt, Font color: Auto, Not

Superscript/ Subscript Formatted: Font color: Auto By calendar week 28 each year each **Network Operator** will provide to **NGET** in writing the forecast information listed in (c) below for the current **Financial Year** and each of the succeeding five **Financial Years**.

(b) Data Providers

In circumstances when the busbar arrangement at a **Grid Supply Point** is expected to be operated in separate sections, separate sets of forecast information for each section will be provided to **NGET**.

(c) Embedded Medium Power Station Output and Demand Control

For the specified time of the annual peak half hour **National Electricity Transmission System Demand**, as specified by **NGET** under PC.A.5.2.2, the output of **Embedded Medium Power Stations** and forecasts of **Demand** to be relieved by **Demand Control** on a **Grid Supply Point** basis giving details of the amount and duration of the **Demand Control**.

OC1.5	DATA REQUIRED BY NGET IN THE PROGRAMMING PHASE, CONTROL PHASE AND POST-CONTROL PHASE				ND	Formatted: Font color: Auto
OC1.5.1	Programming Phase					
	For the period of 2 to 8 weeks ahead the following will be supplied to NGET in writing by 1000 hours each Monday:			by	Formatted: Font: Bold, Font color: Auto	
	(a) <u>Demand Control</u>				Formatted: Font color: Auto	
	Each Network Operator will supply MW profiles of the amount and duration of their proposed use of Demand Control which may result in a Demand change equal to or greater than the Demand Control Notification Level (averaged over any half hour on any Grid Supply Point) on a half hourly and Grid Supply Point basis;					
	(b) Medium Power Station Operation					
		Each Network Operator will, if re the operation of Embedded Med and Grid Supply Point basis.				
OC1.5.2		the period 2 to 12 days ahead the	e following will be sup	oplied to NGET in writing by 12	:00	Formatted: Font color: Auto
	hou	rs each Wednesday:				
	(a)	Demand Control				
	Each Network Operator will supply MW profiles of the amount and duration of their proposed use of Demand Control which may result in a Demand change equal to or greater than the Demand Control Notification Level (averaged over any half hour on any Grid Supply Point) on a half hourly and Grid Supply Point basis;					
	(b) Medium Power Station Operation					
		Each Network Operator will, if re the operation of Embedded Med and Grid Supply Point basis.				
OC1.5.3	Me	dium Power Station Output				Formatted: Font color: Auto
	Each Network Operator will, if reasonably required by NGET , supply NGET with MW schedules for the operation of Embedded Medium Power Stations within its System on a half hourly and Grid Supply Point basis in writing by 1000 hours each day (or such other time specified by NGET from time to time) for the next day (except that it will be for the next 3 days on Fridays and 2 days on Saturdays and may be longer (as specified by NGET at least one week in advance) to cover holiday periods);				n a ner ext	
OC1.5.4	<u>Oth</u>	er Codes				
Issue 5 Revision 0			DC1 of 5	17 August 2	012	

Under OC6 each Network Operator will notify NGET of their proposed use of Demand Control (which may result in a Demand change equal to or greater than the Demand Control Notification Level), and under BC1, each Supplier will notify NGET of their proposed use of Customer Demand Management (which may result in a Demand change equal to or greater than the Customer Demand Management Notification Level) in this timescale.

OC1.5.5 <u>Control Phase</u>

OC1.5.5.1 Demand Control

Under OC6, each Network Operator will notify NGET of any Demand Control proposed by itself which may result in a Demand change equal to or greater than the Demand Control Notification Level averaged over any half hour on any Grid Supply Point which is planned after 1000 hours, and of any changes to the planned Demand Control notified to NGET prior to 1000 hours as soon as possible after the formulation of the new plans;

OC1.5.5.2 Customer Demand Management

- (a) Each Supplier will notify NGET of any Customer Demand Management proposed byitself which may result in a Demand change equal to or greater than the Customer Demand Management Notification Level averaged over any half hour on any Grid Supply Point which is planned to occur at any time in the Control Phase and of any changes to the planned Customer Demand Management already notified to NGET as soon as possible after the formulation of the new plans.
- (b) The following information is required on a Grid Supply Point and half-hourly basis:
 - (i) the proposed date, time and duration of implementation of **Customer Demand Management**; and
 - (ii) the proposed reduction in **Demand** by use of **Customer Demand Management**.

OC1.5.5.3 Load Management Blocks

In Scotland, by 11:00 each day, each **Supplier** who controls a **Load Management Block** of **Demand** with a capacity of 5MW or more shall submit to **NGET** a schedule of its proposed switching times and profiles in respect of each block for the next day.

OC1.5.6 Post-Control Phase

The following will be supplied to **NGET** in writing by 0600 hours each day in respect of **Active Power** data and by 1000 hours each day in respect of **Reactive Power** data:

(a) Demand Control

Each **Network Operator** will supply MW profiles for the previous calendar day of the amount and duration of **Demand** reduction achieved by itself from the use of **Demand Control** equal to or greater than the **Demand Control Notification Level** (averaged over any half hour on any **Grid Supply Point**), on a half hourly and **Grid Supply Point** basis.

(b) Customer Demand Management

Each **Supplier** will supply MW profiles of the amount and duration of **Demand** reduction achieved by itself from the use of **Customer Demand Management** equal to or greater than the **Customer Demand Management Notification Level** (averaged over any half hour on any **Grid Supply Point**) on a half hourly and **Grid Supply Point** basis during the previous calendar day. Formatted: Justified

Formatted: Font color: Auto

Formatted: Font color: Auto

17 August 2012

OC1.6 <u>NGET FORECASTS</u>

OC1.6.1

The following factors will be taken into account by **NGET** when conducting **National Electricity Transmission System Demand** forecasting in the **Programming Phase** and **Control Phase**:

- (a) Historic **Demand** data (this includes **National Electricity Transmission System** Losses).
- (b) Weather forecasts and the current and historic weather conditions.
- (c) The incidence of major events or activities which are known to NGET in advance.
- (d) Anticipated interconnection flows across External Interconnections.
- (e) Demand Control equal to or greater than the Demand Control Notification Level (averaged over any half hour at any Grid Supply Point) proposed to be exercised by Network Operators and of which NGET has been informed.
- (f) Customer Demand Management equal to or greater than the Customer Demand Management Notification Level (averaged over any half hour at any Grid Supply point) proposed to be exercised by Suppliers and of which NGET has been informed.
- (g) Other information supplied by **Users**.
- (h) Anticipated Pumped Storage Unit demand.
- (i) the sensitivity of **Demand** to anticipated market prices for electricity.
- (j) **BM Unit Data** submitted by **BM Participants** to **NGET** in accordance with the provisions of **BC1** and **BC2**.
- (k) Demand taken by Station Transformers
- OC1.6.2 Taking into account the factors specified in OC1.6.1 NGET uses Demand forecast methodology to produce forecasts of National Electricity Transmission System Demand. A written record of the use of the methodology must be kept by NGET for a period of at least 12 months.
- OC1.6.3 The methodology will be based upon factors (a), (b) and (c) above to produce, by statistical means, unbiased forecasts of **National Demand**. **National Electricity Transmission System Demand** will be calculated from these forecasts but will also take into account factors (d), (e), (f), (g), (h), (i) and (j) above. No other factors are taken into account by **NGET**, and it will base its **National Electricity Transmission System Demand** forecasts on those factors only.

< END OF OPERATING CODE NO. 1 >

Formatted: Font color: Auto

Formatted: Left

Issue 5 Revision 0

17 August 2012